

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



CHROMODEN 2K PARQUET OIL

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	28.07.2023	MAT0GE00_061	Date of first issue: 28.07.2023
		HR/EN	

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : CHROMODEN 2K PARQUET OIL

Product code : Please see section 16 for detailed data

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : SU19 Building and construction work
Professional and consumer use of coatings
PC9a Coatings and paints, thinners, paint removers

Recommended restrictions on use : public use, professional use

1.3 Details of the supplier of the safety data sheet

Company : CHROMOS - Boje i lakovi d.d.
Radnička cesta 173D
10000 Zagreb
Croatia

Importer : Helios Hrvatska d.o.o.
Radnička 173/d
10000 Zagreb
Croatia

Telephone Company : 1 241 0666

Telephone Importer : 385 1 46 10 132

Telefax Company : 1 241 5535

Telefax Importer : 385 1 46 12 782

Responsible/issuing person : 1 241 0666
productsafety@chromos.eu

Responsible/issuing person-Importer : 385 1 46 10 132

1.4 Emergency telephone number

Nazvati 112

Broj telefona za medicinske informacije: + 385-01-23-48-342

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



CHROMODEN 2K PARQUET OIL

Version 1.0 Revision Date: 28.07.2023 SDS Number: MAT0GE00_061 HR/EN Date of last issue: - Date of first issue: 28.07.2023

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification REGULATION (EC) No 1272/2008	Concentration (% w/w)
hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics	- 918-481-9 01-2119457273-39	Asp. Tox. 1; H304 EUH066	>= 1 - < 10
reaction mass of α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -hydroxypoly(oxyethylene) and α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxy-poly(oxyethylene)	104810-48-2 400-830-7 607-176-00-3 01-0000015075-76	Skin Sens. 1; H317 Aquatic Chronic 2; H411	>= 0,25 - < 1
Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	1065336-91-5 915-687-0 01-2119491304-40	Skin Sens. 1; H317 Repr. 2; H361f Aquatic Acute 1; H400 Aquatic Chronic 1; H410	>= 0,25 - < 1
2-ethylhexanoic acid, zirconium salt	22464-99-9 245-018-1 01-2119979088-21	Repr. 1B; H360D	>= 0,1 - < 1
2-ethylhexanoic acid, manganese salt	15956-58-8 240-085-3 01-2119979087-23	Eye Irrit. 2; H319 Repr. 1B; H360D STOT RE 2; H373 Aquatic Chronic 2; H411	>= 0,25 - < 1

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.
- If inhaled : If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.
- In case of skin contact : If on skin, rinse well with water.
If on clothes, remove clothes.
- In case of eye contact : Flush eyes with water as a precaution.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



CHROMODEN 2K PARQUET OIL

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	28.07.2023	MAT0GE00_061 HR/EN	Date of first issue: 28.07.2023

If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
Take victim immediately to hospital.

4.2 Most important symptoms and effects, both acute and delayed

None known.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Carbon dioxide (CO₂)

Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
For safety reasons in case of fire, cans should be stored separately in closed containments.
Use a water spray to cool fully closed containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



CHROMODEN 2K PARQUET OIL

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	28.07.2023	MAT0GE00_061 HR/EN	Date of first issue: 28.07.2023

If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).
Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Avoid formation of aerosol.
Do not breathe vapours/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Provide sufficient air exchange and/or exhaust in work rooms.
Dispose of rinse water in accordance with local and national regulations.
Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.

Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material.
Keep away from open flames, hot surfaces and sources of ignition.

Hygiene measures : Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : No smoking. Keep in a well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

Further information on storage stability : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : For further information, refer to the product technical data sheet.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



CHROMODEN 2K PARQUET OIL

Version
1.0

Revision Date:
28.07.2023

SDS Number:
MAT0GE00_061
HR/EN

Date of last issue: -
Date of first issue: 28.07.2023

Consult the technical guidelines for the use of this substance/mixture.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
2-ethylhexanoic acid, zirconium salt	22464-99-9	GVI	5 mg/m ³ (Zirconium)	HR OEL
		STEL	10 mg/m ³ (Zirconium)	HR OEL

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
2-ethylhexanoic acid, zirconium salt	Workers	Inhalation	Long-term systemic effects	32 mg/m ³
	Consumers	Inhalation	Long-term systemic effects	8 mg/m ³
	Consumers	Oral	Long-term systemic effects	2,5 mg/kg bw/day
	Workers	Dermal	Long-term systemic effects	6,49 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	3,25 mg/kg bw/day
	2-ethylhexanoic acid, manganese salt	Workers	Inhalation	Long-term systemic effects
Consumers		Inhalation	Long-term systemic effects	8 mg/m ³
Consumers		Dermal	Long-term systemic effects	2,96 mg/kg bw/day
Workers		Dermal	Long-term systemic effects	5,91 mg/kg bw/day
Consumers		Oral	Long-term systemic effects	2,5 mg/kg bw/day

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
2-ethylhexanoic acid, zirconium salt	Soil	1,06 mg/kg dry weight (d.w.)
	Marine water	0,036 mg/l
	Fresh water	0,36 mg/l
	Marine sediment	0,637 mg/kg dry weight (d.w.)
	Fresh water sediment	6,37 mg/kg dry weight (d.w.)
	Sewage treatment plant	71,7 mg/l
	Intermittent use/release	0,493 mg/l

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



CHROMODEN 2K PARQUET OIL

Version 1.0 Revision Date: 28.07.2023 SDS Number: MAT0GE00_061 HR/EN Date of last issue: - Date of first issue: 28.07.2023

2-ethylhexanoic acid, manganese salt	Soil	1,06 - 25,1 mg/kg dry weight (d.w.)
	Marine water	0,0004 - 0,036 mg/l
	Fresh water	0,0128 - 0,360 mg/l
	Marine sediment	0,00114 - 0,637 mg/kg dry weight (d.w.)
	Fresh water sediment	0,0114 - 6,370 mg/kg dry weight (d.w.)
	Sewage treatment plant	56 - 71,7 mg/l
	Intermittent use/release	0,03 - 0,493 mg/l

8.2 Exposure controls

Personal protective equipment

- Eye/face protection : Equipment should conform to EN 166
Eye wash bottle with pure water
Tightly fitting safety goggles
- Hand protection
- Remarks : Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.
- Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.
- Respiratory protection : Wear a full face respirator conforming to EN136 with Type A/P2 filter or better.
Self-contained open-circuit compressed air breathing apparatus (EN 137)
In the case of aerosol and mist formation use an approved respirator filter (EN 141).

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

- Physical state : liquid
- Colour : in accordance with the product description
- Odour : characteristic
- Odour Threshold : No data available
- Melting point/freezing point : < 0,0 °C (calculation method (principal components, lowest value))
- Boiling point/boiling range : 180 - 220 °C (calculation method (principal components, lowest value))

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



CHROMODEN 2K PARQUET OIL

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	28.07.2023	MAT0GE00_061 HR/EN	Date of first issue: 28.07.2023

Upper explosion limit / Upper flammability limit : 6,1 %(V) (calculation method (principal components, highest value))

Lower explosion limit / Lower flammability limit : 0,6 %(V) (calculation method (principal components, highest value))

Flash point : 65 °C (calculation method (principal components, lowest value))

Not applicable

Decomposition temperature : No decomposition if stored and applied as directed.

pH : No data available

Viscosity

Viscosity, kinematic : > 21 mm²/s (40 °C)

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

Vapour pressure : 50 Pa (calculation method (principal components, highest value))

Relative density : 1,10 (calculation method (principal components, highest value))

Density : 0,88 - 0,98 g/cm³

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



CHROMODEN 2K PARQUET OIL

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	28.07.2023	MAT0GE00_061 HR/EN	Date of first issue: 28.07.2023

Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Not applicable

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Components:

hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics:

Acute oral toxicity	:	LD50 Oral (Rat, male and female): > 5.000 mg/kg Method: OECD Test Guideline 401
Acute inhalation toxicity	:	LC50 (Rat): > 5.000 mg/l Test atmosphere: vapour Method: OECD Test Guideline 403
Acute dermal toxicity	:	LD50 Dermal (Rabbit, male and female): > 5.000 mg/kg Method: OECD Test Guideline 402

Skin corrosion/irritation

Product:

Remarks : May cause skin irritation and/or dermatitis.

Components:

hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics:

Species	:	Rabbit
Method	:	OECD Test Guideline 404
Result	:	No skin irritation
GLP	:	yes
Result	:	Repeated exposure may cause skin dryness or cracking.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



CHROMODEN 2K PARQUET OIL

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	28.07.2023	MAT0GE00_061 HR/EN	Date of first issue: 28.07.2023

Serious eye damage/eye irritation

Product:

Remarks : Vapours may cause irritation to the eyes, respiratory system and the skin.

Components:

hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics:

Species : Rabbit
Method : OECD Test Guideline 405
Result : No eye irritation

2-ethylhexanoic acid, manganese salt:

Result : Eye irritation

Respiratory or skin sensitisation

Product:

Remarks : Causes sensitisation.

Components:

hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics:

Exposure routes : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : Not a skin sensitizer.

mixture of benzotriazole:

Result : Probability or evidence of skin sensitisation in humans

mixture of sterically composed sebacates:

Result : May cause sensitisation by skin contact.

Germ cell mutagenicity

Components:

hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics:

Genotoxicity in vitro : Result: negative
Genotoxicity in vivo : Result: negative

Carcinogenicity

Components:

hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



CHROMODEN 2K PARQUET OIL

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	28.07.2023	MAT0GE00_061 HR/EN	Date of first issue: 28.07.2023

Result : negative

Reproductive toxicity

Components:

hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics:

Effects on foetal development :

mixture of sterically composed sebacates:

Reproductive toxicity - Assessment : Some evidence of adverse effects on sexual function and fertility, based on animal experiments.

STOT - single exposure

Components:

hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics:

Remarks : Based on available data, the classification criteria are not met.

STOT - repeated exposure

Components:

hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics:

Remarks : Based on available data, the classification criteria are not met.

2-ethylhexanoic acid, manganese salt:

Assessment : May cause damage to organs through prolonged or repeated exposure.

Aspiration toxicity

Components:

hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics:

May be fatal if swallowed and enters airways.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



CHROMODEN 2K PARQUET OIL

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	28.07.2023	MAT0GE00_061 HR/EN	Date of first issue: 28.07.2023

Further information

Product:

Remarks : No data available

SECTION 12: Ecological information

12.1 Toxicity

Components:

hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 1.000 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other : EC50 : > 1.000 mg/l
aquatic invertebrates Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae/aquatic : NOEC (Pseudokirchneriella subcapitata (microalgae)): 1.000
plants mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

EC50 (Pseudokirchneriella subcapitata (microalgae)): > 1.000
mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

mixture of benzotriazole:

Ecotoxicology Assessment

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

mixture of sterically composed sebacates:

Ecotoxicology Assessment

Acute aquatic toxicity : Very toxic to aquatic life.

Chronic aquatic toxicity : Very toxic to aquatic life with long lasting effects.

2-ethylhexanoic acid, manganese salt:

Ecotoxicology Assessment

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



CHROMODEN 2K PARQUET OIL

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	28.07.2023	MAT0GE00_061 HR/EN	Date of first issue: 28.07.2023

12.2 Persistence and degradability

Components:

hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 80 %
Exposure time: 28 d
Method: OECD Test Guideline 301F

12.3 Bioaccumulative potential

Components:

mixture of sterically composed sebacates:

Partition coefficient: n-oc- : log Pow: 2,37 - 2,77
tanol/water pH: 7

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Components:

hydrocarbons, C10-C13 n-alkanes, isoalkanes, cyclic, <2% aromatics:

Assessment : This substance is not considered to be persistent, bioaccumulating and toxic (PBT).

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Harmful to aquatic life with long lasting effects.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



CHROMODEN 2K PARQUET OIL

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	28.07.2023	MAT0GE00_061 HR/EN	Date of first issue: 28.07.2023

SECTION 13: Disposal considerations

13.1 Waste treatment methods

- | | | |
|------------------------|---|--|
| Product | : | The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company. |
| Contaminated packaging | : | Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum. |
| Waste Code | : | 08 01 11, waste paint and varnish containing organic solvents or other hazardous substances |
-

SECTION 14: Transport information

14.1 UN number or ID number

- | | | |
|------|---|-----------------------------------|
| ADN | : | Not regulated as a dangerous good |
| ADR | : | Not regulated as a dangerous good |
| RID | : | Not regulated as a dangerous good |
| IMDG | : | Not regulated as a dangerous good |
| IATA | : | Not regulated as a dangerous good |

14.2 UN proper shipping name

- | | | |
|------|---|-----------------------------------|
| ADN | : | Not regulated as a dangerous good |
| ADR | : | Not regulated as a dangerous good |
| RID | : | Not regulated as a dangerous good |
| IMDG | : | Not regulated as a dangerous good |
| IATA | : | Not regulated as a dangerous good |

14.3 Transport hazard class(es)

- | | | |
|------|---|-----------------------------------|
| ADN | : | Not regulated as a dangerous good |
| ADR | : | Not regulated as a dangerous good |
| RID | : | Not regulated as a dangerous good |
| IMDG | : | Not regulated as a dangerous good |
| IATA | : | Not regulated as a dangerous good |

14.4 Packing group

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



CHROMODEN 2K PARQUET OIL

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	28.07.2023	MAT0GE00_061 HR/EN	Date of first issue: 28.07.2023

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA (Cargo) : Not regulated as a dangerous good
IATA (Passenger) : Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59) : N-methyl-2-pyrrolidone
Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable
Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable
REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. : Not applicable

Volatile organic compounds : Directive 2004/42/EC
Volatile organic compounds (VOC) content: 100 g/l

15.2 Chemical safety assessment

A Chemical Safety Assessment is not required for this substance.

SECTION 16: Other information

Full text of H-Statements

H304 : May be fatal if swallowed and enters airways.
H317 : May cause an allergic skin reaction.
H319 : Causes serious eye irritation.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



CHROMODEN 2K PARQUET OIL

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	28.07.2023	MAT0GE00_061 HR/EN	Date of first issue: 28.07.2023

H360D	:	May damage the unborn child.
H361f	:	Suspected of damaging fertility.
H373	:	May cause damage to organs through prolonged or repeated exposure.
H400	:	Very toxic to aquatic life.
H410	:	Very toxic to aquatic life with long lasting effects.
H411	:	Toxic to aquatic life with long lasting effects.
EUH066	:	Repeated exposure may cause skin dryness or cracking.

Full text of other abbreviations

Aquatic Acute	:	Short-term (acute) aquatic hazard
Aquatic Chronic	:	Long-term (chronic) aquatic hazard
Asp. Tox.	:	Aspiration hazard
Eye Irrit.	:	Eye irritation
Repr.	:	Reproductive toxicity
Skin Sens.	:	Skin sensitisation
STOT RE	:	Specific target organ toxicity - repeated exposure
HR OEL	:	Croatia. Regulations on limit values for exposure to hazardous substances at work and on the biological limit values.
HR OEL / STEL	:	Short term exposure limit
HR OEL / GVI	:	time weighted average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECl - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



CHROMODEN 2K PARQUET OIL

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	28.07.2023	MAT0GE00_061 HR/EN	Date of first issue: 28.07.2023

Further information

Classification of the mixture:

Aquatic Chronic 3 H412

Classification procedure:

Calculation method

Material codes (bulk) for which the SDS is valid 430099 , 430314, 430315, 430316, 430317, 430318, 430319, 430320, 430321, 430322, 430323, 430337, 438134, 494180

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.