

FASADEX PUTTY

Fasadex®



PRODUCT DESCRIPTION

Levelling compound in pasty form based on aqueous dispersion of acrylic copolymer and special fillers.

APPLICATION AREA

Levelling and smoothing of exterior and interior walls made of mineral plasters, concrete, plywood panels, chipboards etc.

PROPERTIES

- excellent adhesion to the substrate
- fills unevenness on the substrate (low volume contraction)
- it is elastic and does not crack in a thicker layer
- resistant to weathering
- further processing is possible after 24 hours

APPLICATION TEMPERATURE

+5 °C to +35 °C

THINNING

No thinning required.

SUBSTRATE QUALITY/PREPARATION

The substrate must be firm, clean, free of dust and grease, dry and impregnated with FASADEX SN BOND, FASADEX SINTETIC IMPREGNATION or POLIFLOR IMPREGNATION.

APPLICATION

With metal or plastic trowel in two or more thin layers.

DRYING

4-6 hours for layer thickness up to 3 mm at normal conditions.

CONSUMPTION

0,8-1,5 kg/m², depending on roughness of the substrate.

Last update: April 2021.

Limitation of Liability. The information in this data sheet is based upon laboratory tests we believe to be accurate and is intended for guidance only. All recommendations or suggestions relating to the use of the products made by Chromos, whether in technical documentation or in response to specific enquiry or otherwise are based on data which to the best of our knowledge are reliable. It is end users responsibility to determine the suitability of the product for its intended use. Producer has no control over either the quality or condition of the substrate, or the many factors affecting the use and application of the product. Chromos does therefore not accept any liability arising from loss, injury or damage resulting from such use. The data contained herein are liable to modification as result of practical experience and continuous product development.

Fasadex®



PACKAGING

5, 10 i 25 kg.

STORAGE

In dry and airy rooms at a temperature of + 5 °C to + 25 °C.

Durability: 24 months.

Last update: April 2021.

Limitation of Liability. The information in this data sheet is based upon laboratory tests we believe to be accurate and is intended for guidance only. All recommendations or suggestions relating to the use of the products made by Chromos, whether in technical documentation or in response to specific enquiry or otherwise are based on data which to the best of our knowledge are reliable. It is end users responsibility to determine the suitability of the product for its intended use. Producer has no control over either the quality or condition of the substrate, or the many factors affecting the use and application of the product. Chromos does therefore not accept any liability arising from loss, injury or damage resulting from such use. The data contained herein are liable to modification as result of practical experience and continuous product development.

Chromos boje i lakovi d.d.
Radnička cesta 173d
10000 Zagreb, Hrvatska

Phone: +385 1 2410 666
Fax: +385 1 2405 512
www.chromos.eu

