

FASADEX SILICATE IMPREGNATION

Fasadex®



PRODUCT DESCRIPTION

Primer based on potassium water glass and aqueous dispersion of synthetic binder.

APPLICATION AREA

Impregnating of lime and lime - cement surfaces before applying FASADEX SILICATE PAINT. It is also used as a diluent for FASADEX SILICATE PAINT.

PROPERTIES

- chemically bonds to the substrate and strengthens it
- equalizes and reduces the absorption of the substrate
- improves the adhesion of the new coatings
- reduces the consumption of finishing layers

DENSITY

1050 kg/m³

APPLICATION TEMPERATURE

+8 °C to +35 °C

EU VOC CATEGORY AND LIMITS

IIA (h), 30 g / l (2010); the product contains max. 10 g / l

THINNING

It is diluted with pure water in a 1: 1 ratio (FASADEX SILICATE IMPREGNATION: WATER).

SUBSTRATE QUALITY/ PREPARATION

Remove loose parts, old coats of limestone, oil and grease from the substrate. The facades covered with molds and algae must be repaired by a suitable biocidal agent. Substrate mortar must be hardened, dry and completely carbonated. The substrate must be well insulated from moisture penetration.

APPLICATION METHOD

Apply with a brush or a fur roller in one layer.

Before application, it is necessary to protect glass, window frames and metal objects. Freshly painted facades protect against wind, fog and rain.

Wear suitable protective gloves and face mask / face mask.

Last update: April 2017

Limitation of Liability. The information in this data sheet is based upon laboratory tests we believe to be accurate and is intended for guidance only. All recommendations or suggestions relating to the use of the products made by Chromos, whether in technical documentation or in response to specific enquiry or otherwise are based on data which to the best of our knowledge are reliable. It is end users responsibility to determine the suitability of the product for its intended use. Producer has no control over either the quality or condition of the substrate, or the many factors affecting the use and application of the product. Chromos does therefore not accept any liability arising from loss, injury or damage resulting from such use. The data contained herein are liable to modification as result of practical experience and continuous product development.

Fasadex®



DRYING

At least 24 hours.

CONSUMPTION

0,10-0,13 l/m² (8 -10 m²/l). The consumption depends on the roughness and absorptiveness of the substrate.

PACKAGING

5 l and 15 l.

STORAGE

In dry and airy rooms at a temperature of + 5 °C to + 25 °C.

Durability: 12 months.

Protect from frost!

Last update: April 2017

Limitation of Liability. The information in this data sheet is based upon laboratory tests we believe to be accurate and is intended for guidance only. All recommendations or suggestions relating to the use of the products made by Chromos, whether in technical documentation or in response to specific enquiry or otherwise are based on data which to the best of our knowledge are reliable. It is end users responsibility to determine the suitability of the product for its intended use. Producer has no control over either the quality or condition of the substrate, or the many factors affecting the use and application of the product. Chromos does therefore not accept any liability arising from loss, injury or damage resulting from such use. The data contained herein are liable to modification as result of practical experience and continuous product development.