

FASADEX SILICONE IMPREGNATION W

Fasadex®



PRODUCT DESCRIPTION

Water-based silicone impregnation.

APPLICATION AREA

Impregnation of lime and lime-cement plasters before applying FASADEX SILICONE PAINT.

PROPERTIES

- easy to apply
- penetrates deeply into the substrate and binds loose particles
- does not reduce water vapor diffusion
- is resistant to alkalis and weathering
- It is water repellent

DENSITY

1000 kg/m³

APPLICATION TEMPERATURE

+5 °C to +35 °C

EU VOC CATEGORY AND LIMITS

IIA (h), 30 g / l (2010); the product contains max. 20 g / l

THINNING

It is diluted with pure water in a 1:1 ratio (FASADEX SILICONE IMPREGNATION: WATER).

SUBSTRATE QUALITY/ PREPARATION

The substrate must be dry, clean, firm, free of dust and grease.

APPLICATION METHOD

Apply with a brush, fur roller or spraying in one layer.

DRYING

24 hours under normal conditions.

CONSUMPTION

0,10-0,15 l/m² (6,7 – 10 m²/l) in one layer.

Last update: April 2021.

Limitation of Liability. The information in this data sheet is based upon laboratory tests we believe to be accurate and is intended for guidance only. All recommendations or suggestions relating to the use of the products made by Chromos, whether in technical documentation or in response to specific enquiry or otherwise are based on data which to the best of our knowledge are reliable. It is end users responsibility to determine the suitability of the product for its intended use. Producer has no control over either the quality or condition of the substrate, or the many factors affecting the use and application of the product. Chromos does therefore not accept any liability arising from loss, injury or damage resulting from such use. The data contained herein are liable to modification as result of practical experience and continuous product development.

Fasadex®



PACKAGING

5 l

STORAGE

In dry and airy rooms at a temperature of + 5 °C to + 25 °C.

Durability: 24 months.

Protect from frost!

Last update: April 2021.

Limitation of Liability. The information in this data sheet is based upon laboratory tests we believe to be accurate and is intended for guidance only. All recommendations or suggestions relating to the use of the products made by Chromos, whether in technical documentation or in response to specific enquiry or otherwise are based on data which to the best of our knowledge are reliable. It is end users responsibility to determine the suitability of the product for its intended use. Producer has no control over either the quality or condition of the substrate, or the many factors affecting the use and application of the product. Chromos does therefore not accept any liability arising from loss, injury or damage resulting from such use. The data contained herein are liable to modification as result of practical experience and continuous product development.