

LUXAL DESOL

Luxal®



TYPE OF PRODUCT

Paint remover based on organic solvents mixture.

AREA OF APPLICATION

Used for removal of old or damaged coatings from metal and wooden surfaces.

PROPERTIES

- very high efficiency
- no sagging
- easy removal

DENSITY

920 - 1020 kg/m³ (HRN EN ISO 2811-1:2004)

APPLICATION METHOD

Applied by brush. The softened coating is removed by means of trowel after 3 to 30 minutes (depending on the type of coating and the thickness and number of layers of old paint).

For coatings that are difficult to remove, repeat the procedure.

After processing, metal surface needs to be rinsed with water, dry and protect with the primer.

Wooden surface needs to be sanded with steel wool, allow to dry and then go into further processing wood with putty (if necessary) or with the primer.

THINNING

No thinning.

SPREADING RATE

0,16-0,33 l / m² (3-6 m² /l) per layer.

PACKAGING

Metal can á 0,75 l.

STORAGE

In dry and good ventilated rooms at temperatures from +5 °C to +25 °C.

Shelf life: 2 years.

Last update: March 2017

Limitation of Liability. The information in this data sheet is based upon laboratory tests we believe to be accurate and is intended for guidance only. All recommendations or suggestions relating to the use of the products made by Chromos, whether in technical documentation or in response to specific enquiry or otherwise are based on data which to the best of our knowledge are reliable. It is end users responsibility to determine the suitability of the product for its intended use. Producer has no control over either the quality or condition of the substrate, or the many factors affecting the use and application of the product. Chromos does therefore not accept any liability arising from loss, injury or damage resulting from such use. The data contained herein are liable to modification as result of practical experience and continuous product development.

Luxal®



SAFETY

The information about the safe handling, storage and disposal of products please check in the Safety Data Sheet.

REMARKS

At opening the can please hold up the lid by hand!
Use gloves when you are using the paint removal.

Last update: March 2017

Limitation of Liability. The information in this data sheet is based upon laboratory tests we believe to be accurate and is intended for guidance only. All recommendations or suggestions relating to the use of the products made by Chromos, whether in technical documentation or in response to specific enquiry or otherwise are based on data which to the best of our knowledge are reliable. It is end users responsibility to determine the suitability of the product for its intended use. Producer has no control over either the quality or condition of the substrate, or the many factors affecting the use and application of the product. Chromos does therefore not accept any liability arising from loss, injury or damage resulting from such use. The data contained herein are liable to modification as result of practical experience and continuous product development.