

POLIFLOR EXTRA

Poliflor®



PRODUCT DESCRIPTION

High-coverage interior white paint based on an aqueous dispersion of a synthetic binder.

APPLICATION AREA

Protection and decoration of interior wall surfaces with pronounced unevenness and visible joints, such as gypsum cardboard plates and similar substrates.

PROPERTIES

- excellent coverage
- enables "breathing" of the walls and a healthy indoor climate
- it is resistant to dry wiping
- does not contain solvents and softeners

DENSITY

1640-1670 kg/m³

TINTING/ COLOUR SHADES

Pastel tones from the CHROMOMIX tone chart can be obtained by tinting at points of sale (CHROMOMIX tinting system).

Note:

The maximum permissible deviation of the shade from the standard in CHROMOMIX tone chart or the delivered etalon may be $\Delta E = 2$ (total value of the deviation of the shade, defined according to the CIE2000 model (ISO 7724 / 1-3). When applying the tinted product on larger surfaces, we recommend applying the tinted product of the same production batch and tinting date. For that reason, it is necessary to order the quantity of tinted paint sufficient for coating the entire surface and possible repairs. If this is not possible, we recommend the equalization, ie. mixing the tinted paint needed to coat one surface in one larger container.

Proper preparation of the substrate is very important for a uniform appearance of the shade: impregnating and fine levelling to even out the absorbency and texture of the substrate. During the application, we also do not recommend the additional diluting the tinted paint or mixing it with other products (tinted paints, colorants, and white paint).

APPLICATION TEMPERATURE

+5 °C do +35 °C

Last update: April 2017.

Limitation of Liability. The information in this data sheet is based upon laboratory tests we believe to be accurate and is intended for guidance only. All recommendations or suggestions relating to the use of the products made by Chromos, whether in technical documentation or in response to specific enquiry or otherwise are based on data which to the best of our knowledge are reliable. It is end users responsibility to determine the suitability of the product for its intended use. Producer has no control over either the quality or condition of the substrate, or the many factors affecting the use and application of the product. Chromos does therefore not accept any liability arising from loss, injury or damage resulting from such use. The data contained herein are liable to modification as result of practical experience and continuous product development.

Chromos boje i lakovi d.d.
Radnička cesta 173d
10000 Zagreb, Hrvatska

Phone: +385 1 2410 666
Fax: +385 1 2405 512
www.chromos.eu



Poliflor®



THINNING

With water, cca. 15 % (by volume)

CLASSIFICATION ACCORDING TO EN 13300

Wet abrasion resistance: Class 5

Contrast ratio: Class 2

Gloss: deep mat

Max. grain size: fine

EU VOC CATEGORY AND LIMITS

IIA (a), 30 g/l (2010); the product contains max. 17 g/l

SURFACE QUALITY/ PREPARATION

The surface must be clean, firm, and dry. Highly absorbent substrates should be impregnated with Poliflor impregnation. If necessary, the wall should be finely levelled with Poliflor kit.

APPLICATION

Stir the paint well before use and dilute it with water (around 15 % by volume). Apply the paint in two coats at interval of 4 - 6 hours using a long-fibre fur or textile paint roller, a paint brush or by spraying.

DRYING TIME

The paint is dry for the next coat after 4-6 hours.

CONSUMPTION

0,15- 0,20 l/m² (5 -6,5 m²/l) in two coats. The consumption is dependent on roughness and absorbency of substrate.

PACKAGING

5, 10 i 15 l.

STORAGE

Max. 24 months when stored in originally closed packaging in dry and airy rooms, protected from freezing, high temperatures and direct sunlight.

Last update: April 2017.

Limitation of Liability. The information in this data sheet is based upon laboratory tests we believe to be accurate and is intended for guidance only. All recommendations or suggestions relating to the use of the products made by Chromos, whether in technical documentation or in response to specific enquiry or otherwise are based on data which to the best of our knowledge are reliable. It is end users responsibility to determine the suitability of the product for its intended use. Producer has no control over either the quality or condition of the substrate, or the many factors affecting the use and application of the product. Chromos does therefore not accept any liability arising from loss, injury or damage resulting from such use. The data contained herein are liable to modification as result of practical experience and continuous product development.