

# POLIFLOR FUNGISTOP

Poliflor®



## PRODUCT DESCRIPTION

Aqueous solution of disinfectant with a broad spectrum of action on mould fungi, algae, lichens, and bacteria.

## APPLICATION AREA

Elimination of mould fungi, algae, lichen and bacteria from old wall coatings, plaster, stone, and concrete

## PROPERTIES

- a wide range of effectiveness on different microorganisms
- penetrates deep into the pores of the wall
- destroys mould spores in the pores of the substrate (a complete fungicidal action).

## DENSITY

1000 - 1020 kg/m<sup>3</sup>

## THINNING

No need for thinning.

## SUBSTRATE QUALITY/ PREPARATION

The substrate must be dry, firm, free of grease and dust. All loose parts should be removed from old substrates. Any repairs to the substrate should be performed with POLIFLOR KIT or FASADDEX KIT. Gypsum-containing putties must not be used.

## APPLICATION

Apply by brush to ensure the best penetration into the substrate. If the substrate is heavily attacked with mould fungi, the procedure should be repeated, to ensure that the moulds are destroyed. Once the walls are dry, the mould needs to be removed mechanically.

## DRYING

At least 12 hours at normal conditions.

Last update: June 2021.

Limitation of Liability. The information in this data sheet is based upon laboratory tests we believe to be accurate and is intended for guidance only. All recommendations or suggestions relating to the use of the products made by Chromos, whether in technical documentation or in response to specific enquiry or otherwise are based on data which to the best of our knowledge are reliable. It is end users responsibility to determine the suitability of the product for its intended use. Producer has no control over either the quality or condition of the substrate, or the many factors affecting the use and application of the product. Chromos does therefore not accept any liability arising from loss, injury or damage resulting from such use. The data contained herein are liable to modification as result of practical experience and continuous product development.

**Poliflor®**



#### CONSUMPTION

0,16- 0,25 l/m<sup>2</sup> (4 -6 m<sup>2</sup>/l), in one coat.

#### PACKAGING

1, 5 and 20 l.

#### STORAGE

Max. 24 months when stored in originally closed packaging in dry and airy rooms, protected from freezing, high temperatures and direct sunlight

#### NOTE

The use of goggles and rubber gloves is mandatory when applying the impregnation.

Last update: June 2021.

Limitation of Liability. The information in this data sheet is based upon laboratory tests we believe to be accurate and is intended for guidance only. All recommendations or suggestions relating to the use of the products made by Chromos, whether in technical documentation or in response to specific enquiry or otherwise are based on data which to the best of our knowledge are reliable. It is end users responsibility to determine the suitability of the product for its intended use. Producer has no control over either the quality or condition of the substrate, or the many factors affecting the use and application of the product. Chromos does therefore not accept any liability arising from loss, injury or damage resulting from such use. The data contained herein are liable to modification as result of practical experience and continuous product development.

**Chromos boje i lakovi d.d.**  
Radnička cesta 173d  
10000 Zagreb, Hrvatska

Phone: +385 1 2410 666  
Fax: +385 1 2405 512  
[www.chromos.eu](http://www.chromos.eu)

 **Chromos**