

# POLIFLOR PUROLIT

Poliflor®



## PRODUCT DESCRIPTION

Paint on the basis of an acrylic resin in an organic solvent.

## APPLICATION AREA

Repair of interior wall surfaces with water stains, nicotine stains, aniline paintings etc.

## PROPERTIES

- easy to apply
- covers and insulate stains on the substrate
- quick drying

## DENSITY

1670-1750 kg/m<sup>3</sup>

## APPLICATION TEMPERATURE

-30 °C do +35 °C

## TINTING

Not necessary

## EU VOC CATEGORY AND LIMITS

IIA (g), 350 g / l (2010); the product contains max. 350 g / l

## THINNING

No thinning needed.

## SUBSTRATE QUALITY/ PREPARATION

The substrate must be firm, clean, dry, and dusted off.

## APPLICATION METHOD

With a brush or a fur roller in one layer. If necessary, another layer may be applied. It is recommended to apply Poliflor purolit on the stain and, after the coat is dried, paint the entire surface with dispersion paint.

After use, the tool can be cleaned with Luxal syntetic thinner.

Last update: April 2017.

Limitation of Liability. The information in this data sheet is based upon laboratory tests we believe to be accurate and is intended for guidance only. All recommendations or suggestions relating to the use of the products made by Chromos, whether in technical documentation or in response to specific enquiry or otherwise are based on data which to the best of our knowledge are reliable. It is end users responsibility to determine the suitability of the product for its intended use. Producer has no control over either the quality or condition of the substrate, or the many factors affecting the use and application of the product. Chromos does therefore not accept any liability arising from loss, injury or damage resulting from such use. The data contained herein are liable to modification as result of practical experience and continuous product development.

Chromos boje i lakovi d.d.  
Radnička cesta 173d  
10000 Zagreb, Hrvatska

Phone: +385 1 2410 666  
Fax: +385 1 2405 512  
www.chromos.eu



**Poliflor®**



#### DRYING

1 h under standard conditions.

#### CONSUMPTION

0,16 l/m<sup>2</sup> (oko 6 m<sup>2</sup>/l) in one layer.

#### PACKAGING

0,75 l.

#### STORAGE

In dry and airy rooms at a temperature of + 5 °C to + 25 °C.  
Durability: 3 years.

Last update: April 2017.

Limitation of Liability. The information in this data sheet is based upon laboratory tests we believe to be accurate and is intended for guidance only. All recommendations or suggestions relating to the use of the products made by Chromos, whether in technical documentation or in response to specific enquiry or otherwise are based on data which to the best of our knowledge are reliable. It is end users responsibility to determine the suitability of the product for its intended use. Producer has no control over either the quality or condition of the substrate, or the many factors affecting the use and application of the product. Chromos does therefore not accept any liability arising from loss, injury or damage resulting from such use. The data contained herein are liable to modification as result of practical experience and continuous product development.

**Chromos boje i lakovi d.d.**  
Radnička cesta 173d  
10000 Zagreb, Hrvatska

Phone: +385 1 2410 666  
Fax: +385 1 2405 512  
[www.chromos.eu](http://www.chromos.eu)

 **Chromos**