

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## FLOOR EXPERT EP 311 KOMP B , 101E KOMP B



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	08.06.2022	MAT0GE00_005 HR / EN	Date of first issue: 08.06.2022

---

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : FLOOR EXPERT EP 311 KOMP B , 101E KOMP B

Product code : Please see section 16 for detailed data

Unique Formula Identifier (UFI) : F3RG-67N2-M10C-X4Q8

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : SU19 Building and construction work  
SU22 Professional uses  
PC9a Coatings and paints, thinners, paint removers

Recommended restrictions on use : professional use

#### 1.3 Details of the supplier of the safety data sheet

Company : CHROMOS - Boje i lakovi d.d.  
Radnička cesta 173D  
10000 Zagreb  
Croatia

Telephone Company : 1 241 0666

Telefax Company : 1 241 5535

Responsible/issuing person : 1 241 0666  
productsafety@chromos.eu

#### 1.4 Emergency telephone number

Nazvati 112

Broj telefona za medicinske informacije: + 385-01-23-48-342

---

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification REGULATION (EC) No 1272/2008

Acute toxicity, Category 4	H302: Harmful if swallowed.
Skin corrosion, Sub-category 1B	H314: Causes severe skin burns and eye damage.
Serious eye damage, Category 1	H318: Causes serious eye damage.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## FLOOR EXPERT EP 311 KOMP B , 101E KOMP B

Version 1.0	Revision Date: 08.06.2022	SDS Number: MAT0GE00_005 HR / EN	Date of last issue: - Date of first issue: 08.06.2022
----------------	------------------------------	--	--

Skin sensitisation, Category 1  
Long-term (chronic) aquatic hazard, Category 3

H317: May cause an allergic skin reaction.  
H412: Harmful to aquatic life with long lasting effects.

### 2.2 Label elements

#### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

Hazard statements : H302 Harmful if swallowed.  
H314 Causes severe skin burns and eye damage.  
H317 May cause an allergic skin reaction.  
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements : **Prevention:**  
P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.  
P273 Avoid release to the environment.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

#### **Response:**

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.  
P304 + P340 + P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/ doctor.  
P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.

#### **Hazardous components which must be listed on the label:**

3-aminomethyl-3,5,5-trimethylcyclohexylamine  
benzyl alcohol  
m-phenylenebis(methylamine)

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## FLOOR EXPERT EP 311 KOMP B , 101E KOMP B

Version 1.0      Revision Date: 08.06.2022      SDS Number: MAT0GE00\_005 HR / EN      Date of last issue: -      Date of first issue: 08.06.2022

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### SECTION 3: Composition/information on ingredients

#### 3.2 Mixtures

Chemical nature : Mixture

#### Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification REGULATION (EC) No 1272/2008	Concentration (% w/w)
3-aminomethyl-3,5,5-trimethylcyclohexylamine	2855-13-2 220-666-8 612-067-00-9 01-2119514687-32	Acute Tox. 4; H302 Acute Tox. 4; H312 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Chronic 3; H412  specific concentration limit Skin Sens. 1A; H317 >= 0,001 %	>= 30 - < 50
benzyl alcohol	100-51-6 202-859-9 603-057-00-5 01-2119492630-38	Acute Tox. 4; H302 Acute Tox. 4; H332	>= 30 - < 50
m-phenylenebis(methylamine)	1477-55-0 216-032-5 01-2119480150-50	Acute Tox. 4; H302 Acute Tox. 4; H332 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Chronic 3; H412	>= 10 - < 20

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

General advice : Move out of dangerous area.  
Consult a physician.  
Show this safety data sheet to the doctor in attendance.  
Do not leave the victim unattended.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## FLOOR EXPERT EP 311 KOMP B , 101E KOMP B



Version 1.0	Revision Date: 08.06.2022	SDS Number: MAT0GE00_005 HR / EN	Date of last issue: - Date of first issue: 08.06.2022
----------------	------------------------------	--	--

- If inhaled : If unconscious, place in recovery position and seek medical advice.  
If symptoms persist, call a physician.
- In case of skin contact : Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficulty.  
If on skin, rinse well with water.  
If on clothes, remove clothes.
- In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.  
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.  
Continue rinsing eyes during transport to hospital.  
Remove contact lenses.  
Protect unharmed eye.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.  
Do NOT induce vomiting.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.  
Take victim immediately to hospital.

### 4.2 Most important symptoms and effects, both acute and delayed

None known.

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Unsuitable extinguishing media : High volume water jet

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.

### 5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## FLOOR EXPERT EP 311 KOMP B , 101E KOMP B



Version 1.0	Revision Date: 08.06.2022	SDS Number: MAT0GE00_005 HR / EN	Date of last issue: - Date of first issue: 08.06.2022
----------------	------------------------------	--	--

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

#### 6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.

#### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Keep in suitable, closed containers for disposal.

#### 6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

### SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

Advice on safe handling : Do not breathe vapours/dust.  
Avoid exposure - obtain special instructions before use.  
Avoid contact with skin and eyes.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
To avoid spills during handling keep bottle on a metal tray.  
Dispose of rinse water in accordance with local and national regulations.  
Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Hygiene measures : When using do not eat or drink. When using do not smoke.  
Wash hands before breaks and at the end of workday.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## FLOOR EXPERT EP 311 KOMP B , 101E KOMP B



Version 1.0	Revision Date: 08.06.2022	SDS Number: MAT0GE00_005 HR / EN	Date of last issue: - Date of first issue: 08.06.2022
----------------	------------------------------	--	--

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully re-sealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

Further information on storage stability : No decomposition if stored and applied as directed.

### 7.3 Specific end use(s)

Specific use(s) : For further information, refer to the product technical data sheet.

Consult the technical guidelines for the use of this substance/mixture.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

Contains no substances with occupational exposure limit values.

#### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
3-aminomethyl-3,5,5-trimethylcyclohexylamine	Workers	Inhalation	Long-term local effects	0,073 mg/m <sup>3</sup>
	Workers	Inhalation	Acute local effects	0,073 mg/m <sup>3</sup>
	Consumers	Oral	Long-term systemic effects	0,526 mg/kg bw/day
benzyl alcohol	Workers	Inhalation	Long-term systemic effects	22 mg/m <sup>3</sup>
	Workers	Inhalation	Acute systemic effects	110 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term systemic effects	5,4 mg/m <sup>3</sup>
	Workers	Inhalation	Acute systemic effects	27 mg/m <sup>3</sup>
	Workers	Inhalation	Acute systemic effects	27 mg/m <sup>3</sup>
	Workers	Dermal	Long-term systemic effects	8 mg/kg bw/day
Workers	Dermal	Acute systemic effects	40 mg/kg bw/day	
	Dermal	Long-term systemic effects	4 mg/kg bw/day	
	Consumers	Dermal	Acute systemic effects	20 mg/kg bw/day

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## FLOOR EXPERT EP 311 KOMP B , 101E KOMP B



Version  
1.0

Revision Date:  
08.06.2022

SDS Number:  
MAT0GE00\_005  
HR / EN

Date of last issue: -  
Date of first issue: 08.06.2022

	Consumers	Oral	Long-term systemic effects	4 mg/kg bw/day
	Consumers	Oral	Acute systemic effects	20 mg/kg bw/day
m-phenylenebis(methylamine)	Workers	Inhalation	Long-term systemic effects	1,2 mg/m3
	Workers	Inhalation	Long-term systemic effects	1,2 mg/m3
	Workers	Inhalation	Long-term local effects	0,2 mg/m3
	Workers	Inhalation	Long-term local effects	0,2 mg/m3
	Workers	Dermal	Long-term systemic effects	0,33 mg/m3
	Workers	Dermal	Long-term systemic effects	0,33 mg/m3

### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
3-aminomethyl-3,5,5-trimethylcyclohexylamine	Soil	1,121 mg/kg dry weight (d.w.)
	Marine water	0,006 mg/l
	Fresh water	0,06 mg/l
	Marine sediment	0,578 mg/kg dry weight (d.w.)
	Fresh water sediment	5,784 mg/kg dry weight (d.w.)
	Sewage treatment plant	3,18 mg/l
	Intermittent use/release	0,23 mg/l
benzyl alcohol	Soil	0,456 mg/kg dry weight (d.w.)
	Marine water	0,1 mg/l
	Fresh water	1 mg/l
	Marine sediment	0,527 mg/kg dry weight (d.w.)
	Fresh water sediment	5,27 mg/kg dry weight (d.w.)
	Sewage treatment plant	39 mg/l
m-phenylenebis(methylamine)	Intermittent use/release	2,3 mg/l
	Soil	0,045 mg/kg dry weight (d.w.)
	Soil	0,045 mg/kg dry weight (d.w.)
	Marine water	0,0094 mg/l
	Marine water	0,0094 mg/l
	Fresh water	0,094 mg/l
	Fresh water	0,094 mg/l
	Marine sediment	0,043 mg/kg dry weight (d.w.)
	Marine sediment	0,043 mg/kg dry weight (d.w.)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## FLOOR EXPERT EP 311 KOMP B , 101E KOMP B



Version 1.0      Revision Date: 08.06.2022      SDS Number: MAT0GE00\_005 HR / EN      Date of last issue: -      Date of first issue: 08.06.2022

	Fresh water sediment	0,43 mg/kg dry weight (d.w.)
	Fresh water sediment	0,43 mg/kg dry weight (d.w.)
	Sewage treatment plant	10 mg/l
	Sewage treatment plant	10 mg/l
	Intermittent use/release	0,152 mg/l
	Intermittent use/release	0,152 mg/l

### 8.2 Exposure controls

#### Personal protective equipment

Eye protection : Equipment should conform to EN 166  
Eye wash bottle with pure water  
Tightly fitting safety goggles  
Wear face-shield and protective suit for abnormal processing problems.

Hand protection

Remarks : Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.

Skin and body protection : Impervious clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.  
In the case of dust or aerosol formation use respirator with an approved filter.

Respirator with a half face mask

Equipment should conform to EN-136; EN-143; EN-149; EN-529

Filter type : Combined particulates and organic vapour type (A - P2)

### SECTION 9: Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

Physical state : liquid  
Colour : in accordance with the product description  
Odour : characteristic  
Odour Threshold : No data available

Melting point/freezing point : -15,4 °C  
(calculation method (principal components, lowest value))

Boiling point/boiling range : 205 °C (calculation method (principal components, lowest value))  
(1.013,25 hPa)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## FLOOR EXPERT EP 311 KOMP B , 101E KOMP B



Version 1.0	Revision Date: 08.06.2022	SDS Number: MAT0GE00_005 HR / EN	Date of last issue: - Date of first issue: 08.06.2022
----------------	------------------------------	--	--

---

Ignition temperature : 436 °C  
(calculation method (principal components, highest value))

Decomposition temperature : No decomposition if stored and applied as directed.

pH : No data available

Viscosity

Viscosity, dynamic : 400 mPa.s

Viscosity, kinematic : > 21 mm<sup>2</sup>/s (40 °C)

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : log Pow: 1,1  
(calculation method (principal components, highest value))

Vapour pressure : 0,03 hPa  
(calculation method (principal components, highest value))  
(20 °C)

Relative density : 1,18  
(calculation method (principal components, highest value))

Density : 1,0 g/cm<sup>3</sup>

Relative vapour density : 5,9  
(calculation method (principal components, lowest value))  
  
(Air = 1.0)

### 9.2 Other information

No data available

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No decomposition if stored and applied as directed.

### 10.2 Chemical stability

No decomposition if stored and applied as directed.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## FLOOR EXPERT EP 311 KOMP B , 101E KOMP B



Version 1.0	Revision Date: 08.06.2022	SDS Number: MAT0GE00_005 HR / EN	Date of last issue: - Date of first issue: 08.06.2022
----------------	------------------------------	--	--

---

### 10.4 Conditions to avoid

Conditions to avoid : No data available

### 10.5 Incompatible materials

Materials to avoid : Not applicable

### 10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

---

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

##### Product:

Acute oral toxicity : Acute toxicity estimate: 655,05 mg/kg  
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2.000 mg/kg  
Method: Calculation method

##### Components:

#### **3-aminomethyl-3,5,5-trimethylcyclohexylamine:**

Acute oral toxicity : LD50 (Rat): 1.030 mg/kg  
Method: OECD Test Guideline 401  
Assessment: The component/mixture is moderately toxic after single ingestion.

Acute dermal toxicity : LD50 (Rat): 2.000 mg/kg  
Method: OECD Test Guideline 402

#### **benzyl alcohol:**

Acute oral toxicity : Assessment: The component/mixture is moderately toxic after single ingestion.

Acute inhalation toxicity : Test atmosphere: vapour  
Assessment: The component/mixture is moderately toxic after short term inhalation.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## FLOOR EXPERT EP 311 KOMP B , 101E KOMP B



Version 1.0	Revision Date: 08.06.2022	SDS Number: MAT0GE00_005 HR / EN	Date of last issue: - Date of first issue: 08.06.2022
----------------	------------------------------	--	--

---

### **m-phenylenebis(methylamine):**

Acute oral toxicity : Assessment: The component/mixture is moderately toxic after single ingestion.

Acute inhalation toxicity : Assessment: The component/mixture is moderately toxic after short term inhalation.

### **Skin corrosion/irritation**

#### **Product:**

Remarks : Extremely corrosive and destructive to tissue.

#### **Components:**

##### **3-aminomethyl-3,5,5-trimethylcyclohexylamine:**

Result : Corrosive after 3 minutes to 1 hour of exposure

##### **m-phenylenebis(methylamine):**

Result : Corrosive after 3 minutes to 1 hour of exposure

### **Serious eye damage/eye irritation**

#### **Product:**

Remarks : May cause irreversible eye damage.

### **Respiratory or skin sensitisation**

#### **Product:**

Remarks : Causes sensitisation.

#### **Components:**

##### **3-aminomethyl-3,5,5-trimethylcyclohexylamine:**

Result : Probability or evidence of skin sensitisation in humans

##### **m-phenylenebis(methylamine):**

Result : Probability or evidence of skin sensitisation in humans

## **11.2 Information on other hazards**

### **Endocrine disrupting properties**

#### **Product:**

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## FLOOR EXPERT EP 311 KOMP B , 101E KOMP B



Version 1.0	Revision Date: 08.06.2022	SDS Number: MAT0GE00_005 HR / EN	Date of last issue: - Date of first issue: 08.06.2022
----------------	------------------------------	--	--

(EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### Further information

#### Product:

Remarks : No data available

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Components:

##### **3-aminomethyl-3,5,5-trimethylcyclohexylamine:**

Toxicity to fish : LC50 (Fish):  $\geq$  110 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia (water flea)): 23 mg/l

Toxicity to algae/aquatic plants : EC50 (algae):  $\geq$  22 mg/l

#### **Ecotoxicology Assessment**

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

##### **m-phenylenebis(methylamine):**

#### **Ecotoxicology Assessment**

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

### 12.2 Persistence and degradability

No data available

### 12.3 Bioaccumulative potential

#### Components:

##### **3-aminomethyl-3,5,5-trimethylcyclohexylamine:**

Partition coefficient: n-octanol/water : log Pow: 0,79

##### **benzyl alcohol:**

Partition coefficient: n-octanol/water : log Pow: 1,1

### 12.4 Mobility in soil

No data available

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## FLOOR EXPERT EP 311 KOMP B , 101E KOMP B



Version 1.0	Revision Date: 08.06.2022	SDS Number: MAT0GE00_005 HR / EN	Date of last issue: - Date of first issue: 08.06.2022
----------------	------------------------------	--	--

---

### 12.5 Results of PBT and vPvB assessment

**Product:**

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

### 12.6 Endocrine disrupting properties

**Product:**

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### 12.7 Other adverse effects

**Product:**

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.  
Harmful to aquatic life with long lasting effects.

---

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water courses or the soil.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.

Waste Code : 08 01 11\*, waste paint and varnish containing organic solvents or other hazardous substances

---

## SECTION 14: Transport information

### 14.1 UN number or ID number

ADN : UN 2735  
ADR : UN 2735

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## FLOOR EXPERT EP 311 KOMP B , 101E KOMP B



Version 1.0	Revision Date: 08.06.2022	SDS Number: MAT0GE00_005 HR / EN	Date of last issue: - Date of first issue: 08.06.2022
----------------	------------------------------	--	--

**RID** : UN 2735  
**IMDG** : UN 2735  
**IATA** : UN 2735

### 14.2 UN proper shipping name

**ADN** : AMINES, LIQUID, CORROSIVE, N.O.S.  
(ISOPHORONDIAMIN, m-phenylenebis(methylamine))  
**ADR** : AMINES, LIQUID, CORROSIVE, N.O.S.  
(ISOPHORONDIAMIN, m-phenylenebis(methylamine))  
**RID** : AMINES, LIQUID, CORROSIVE, N.O.S.  
(ISOPHORONDIAMIN, m-phenylenebis(methylamine))  
**IMDG** : AMINES, LIQUID, CORROSIVE, N.O.S.  
(ISOPHORONDIAMIN, m-phenylenebis(methylamine))  
**IATA** : Amines, liquid, corrosive, n.o.s.  
(ISOPHORONDIAMIN, m-phenylenebis(methylamine))

### 14.3 Transport hazard class(es)

**ADN** : 8  
**ADR** : 8  
**RID** : 8  
**IMDG** : 8  
**IATA** : 8

### 14.4 Packing group

**ADN**  
Packing group : II  
Classification Code : C7  
Hazard Identification Number : 80  
Labels : 8

**ADR**  
Packing group : II  
Classification Code : C7  
Hazard Identification Number : 80  
Labels : 8  
Tunnel restriction code : (E)

**RID**  
Packing group : II  
Classification Code : C7  
Hazard Identification Number : 80  
Labels : 8

**IMDG**  
Packing group : II  
Labels : 8  
EmS Code : F-A, S-B

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## FLOOR EXPERT EP 311 KOMP B , 101E KOMP B



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	08.06.2022	MAT0GE00_005 HR / EN	Date of first issue: 08.06.2022

### IATA (Cargo)

Packing instruction (cargo aircraft) : 855  
Packing instruction (LQ) : Y840  
Packing group : II  
Labels : Corrosive

### IATA (Passenger)

Packing instruction (passenger aircraft) : 851  
Packing instruction (LQ) : Y840  
Packing group : II  
Labels : Corrosive

### 14.5 Environmental hazards

#### ADN

Environmentally hazardous : no

#### ADR

Environmentally hazardous : no

#### RID

Environmentally hazardous : no

#### IMDG

Marine pollutant : no

### 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. Not applicable

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)  
Not applicable

### 15.2 Chemical safety assessment

A Chemical Safety Assessment is not required for this substance.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## FLOOR EXPERT EP 311 KOMP B , 101E KOMP B

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	08.06.2022	MAT0GE00_005 HR / EN	Date of first issue: 08.06.2022

### SECTION 16: Other information

#### Full text of H-Statements

H302	:	Harmful if swallowed.
H312	:	Harmful in contact with skin.
H314	:	Causes severe skin burns and eye damage.
H317	:	May cause an allergic skin reaction.
H318	:	Causes serious eye damage.
H332	:	Harmful if inhaled.
H412	:	Harmful to aquatic life with long lasting effects.

#### Full text of other abbreviations

Acute Tox.	:	Acute toxicity
Aquatic Chronic	:	Long-term (chronic) aquatic hazard
Eye Dam.	:	Serious eye damage
Skin Corr.	:	Skin corrosion
Skin Sens.	:	Skin sensitisation

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECl - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## FLOOR EXPERT EP 311 KOMP B , 101E KOMP B



Version 1.0	Revision Date: 08.06.2022	SDS Number: MAT0GE00_005 HR / EN	Date of last issue: - Date of first issue: 08.06.2022
----------------	------------------------------	--	--

---

### Further information

#### Classification of the mixture:

Acute Tox. 4	H302
Skin Corr. 1B	H314
Eye Dam. 1	H318
Skin Sens. 1	H317
Aquatic Chronic 3	H412

#### Classification procedure:

Calculation method
Calculation method
Calculation method
Calculation method
Calculation method

Material codes (bulk) for which the SDS is valid                      431033 , 437892

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.