

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## THINNER 10

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10.01.2025	MAT0GE00_021 HR/EN	Date of first issue: 10.01.2025

---

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : THINNER 10

Product code : Please see section 16 for detailed data

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : SU19: Building and construction work  
: Professional and consumer use of coatings  
PC9a: Coatings and paints, thinners, paint removers

Recommended restrictions on use : public use, professional use

#### 1.3 Details of the supplier of the safety data sheet

Company : CHROMOS - Boje i lakovi d.d.  
Radnička cesta 173D  
10000 Zagreb  
Croatia

Importer : KANSAI HELIOS Croatia d.o.o.  
Radnička 173/d  
10000 Zagreb  
Croatia

Telephone Company : 1 241 0666

Telephone Importer : 385 1 46 10 132

Telefax Company : 1 241 5535

Telefax Importer : 385 1 46 12 782

Responsible/issuing person : 1 241 0666  
productsafety@chromos.eu

Responsible/issuing person-Importer : 385 1 46 10 132

#### 1.4 Emergency telephone number

Nazvati 112

Broj telefona za medicinske informacije: + 385-01-23-48-342

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## THINNER 10

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10.01.2025	MAT0GE00_021 HR/EN	Date of first issue: 10.01.2025

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification REGULATION (EC) No 1272/2008

Flammable liquids, Category 2	H225: Highly flammable liquid and vapour.
Acute toxicity, Category 4	H332: Harmful if inhaled.
Acute toxicity, Category 4	H312: Harmful in contact with skin.
Skin irritation, Category 2	H315: Causes skin irritation.
Serious eye damage, Category 1	H318: Causes serious eye damage.
Specific target organ toxicity - single exposure, Category 3, Central nervous system	H336: May cause drowsiness or dizziness.
Specific target organ toxicity - single exposure, Category 3, Respiratory system	H335: May cause respiratory irritation.
Specific target organ toxicity - repeated exposure, Category 2	H373: May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard, Category 1	H304: May be fatal if swallowed and enters airways.

#### 2.2 Label elements

##### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms	:	
Signal word	:	Danger
Hazard statements	:	H225 Highly flammable liquid and vapour. H304 May be fatal if swallowed and enters airways. H312 + H332 Harmful in contact with skin or if inhaled. H315 Causes skin irritation. H318 Causes serious eye damage. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H373 May cause damage to organs through prolonged or repeated exposure.
Precautionary statements	:	P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children.
<b>Prevention:</b>		
	:	P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray. P271 Use only outdoors or in a well-ventilated area. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## THINNER 10

Version 1.0      Revision Date: 10.01.2025      SDS Number: MAT0GE00\_021 HR/EN      Date of last issue: -  
Date of first issue: 10.01.2025

### Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.

P331 Do NOT induce vomiting.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

### Storage:

P405 Store locked up.

### Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

### Hazardous components which must be listed on the label:

reaction mixture of ethylbenzene, m-xylene and p-xylene  
2-methylpropan-1-ol

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

Chemical nature : Paint related material

#### Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification REGULATION (EC) No 1272/2008	Concentration (% w/w)
reaction mixture of ethylbenzene, m-xylene and p-xylene	- 905-562-9 01-2119555267-33	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315	>= 70 - < 90

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## THINNER 10

Version 1.0      Revision Date: 10.01.2025      SDS Number: MAT0GE00\_021 HR/EN      Date of last issue: -  
Date of first issue: 10.01.2025

		Eye Irrit. 2; H319 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 Asp. Tox. 1; H304	
2-methylpropan-1-ol	78-83-1 201-148-0 603-108-00-1 01-2119484609-23	Flam. Liq. 3; H226 Skin Irrit. 2; H315 Eye Dam. 1; H318 STOT SE 3; H336 (Central nervous system) STOT SE 3; H335 (Respiratory system)	>= 20 - < 30

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- General advice : Move out of dangerous area.  
Consult a physician.  
Show this safety data sheet to the doctor in attendance.  
Symptoms of poisoning may appear several hours later.  
Do not leave the victim unattended.
- If inhaled : Consult a physician after significant exposure.  
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : If skin irritation persists, call a physician.  
If on skin, rinse well with water.  
If on clothes, remove clothes.
- In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.  
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.  
Continue rinsing eyes during transport to hospital.  
Remove contact lenses.  
Protect unharmed eye.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.  
Do NOT induce vomiting.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.  
Take victim immediately to hospital.

#### 4.2 Most important symptoms and effects, both acute and delayed

None known.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## THINNER 10

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10.01.2025	MAT0GE00_021 HR/EN	Date of first issue: 10.01.2025

---

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

---

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media : Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical

Unsuitable extinguishing media : High volume water jet

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.

### 5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.  
For safety reasons in case of fire, cans should be stored separately in closed containments.  
Use a water spray to cool fully closed containers.

---

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.  
Ensure adequate ventilation.  
Remove all sources of ignition.  
Evacuate personnel to safe areas.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

### 6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.

---

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## THINNER 10

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10.01.2025	MAT0GE00_021 HR/EN	Date of first issue: 10.01.2025

---

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

### 6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

---

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Advice on safe handling : Avoid formation of aerosol.  
Do not breathe vapours/dust.  
Avoid exposure - obtain special instructions before use.  
Avoid contact with skin and eyes.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Take precautionary measures against static discharges.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Open drum carefully as content may be under pressure.  
To avoid spills during handling keep bottle on a metal tray.  
Dispose of rinse water in accordance with local and national regulations.

Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material.  
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.

Hygiene measures : When using do not eat or drink. When using do not smoke.  
Wash hands before breaks and at the end of workday.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

Further information on storage stability : No decomposition if stored and applied as directed.

### 7.3 Specific end use(s)

Specific use(s) : For further information, refer to the product technical data sheet.

Consult the technical guidelines for the use of this substance/mixture.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## THINNER 10

Version 1.0      Revision Date: 10.01.2025      SDS Number: MAT0GE00\_021 HR/EN      Date of last issue: -  
Date of first issue: 10.01.2025

### SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

##### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
reaction mixture of ethylbenzene, m-xylene and p-xylene	1330-20-7	TWA	50 ppm 221 mg/m <sup>3</sup>	2000/39/EC
		Further information: Identifies the possibility of significant uptake through the skin, Indicative		
		STEL	100 ppm 442 mg/m <sup>3</sup>	2000/39/EC
		Further information: Identifies the possibility of significant uptake through the skin, Indicative		
		GVI	50 ppm 221 mg/m <sup>3</sup>	HR OEL
		Further information: Classified as a substance that irritates the skin (H315) or such notice is given in the directives, 2000/39/EU		
		STEL	100 ppm 442 mg/m <sup>3</sup>	HR OEL
		Further information: Classified as a substance that irritates the skin (H315) or such notice is given in the directives, 2000/39/EU		
2-methylpropan-1-ol	78-83-1	GVI	50 ppm 154 mg/m <sup>3</sup>	HR OEL
		Further information: Classified as a substance that irritates the skin (H315) or such notice is given in the directives		
		STEL	75 ppm 231 mg/m <sup>3</sup>	HR OEL
		Further information: Classified as a substance that irritates the skin (H315) or such notice is given in the directives		

##### Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
reaction mixture of ethylbenzene, m-xylene and p-xylene	1330-20-7	xylene: 14.13 micromol per litre (Blood)	End of shift	HR BEI
		xylene: 1,5 mg/l (Blood)	End of shift	HR BEI
		methyl hippuric acid: 0.88 mol/mol creatinine (Urine)	End of shift	HR BEI
		methyl hippuric acid: 1.5 g/g creatinine (Urine)	End of shift	HR BEI

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## THINNER 10

Version 1.0      Revision Date: 10.01.2025      SDS Number: MAT0GE00\_021 HR/EN      Date of last issue: -  
Date of first issue: 10.01.2025

### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
reaction mixture of ethylbenzene, m-xylene and p-xylene	Workers	Inhalation	Long-term systemic effects	77 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term local effects	65,3 mg/m <sup>3</sup>
	Workers	Inhalation	Acute systemic effects	442 mg/m <sup>3</sup>
	Workers	Inhalation	Acute local effects	289 mg/m <sup>3</sup>
	Consumers	Inhalation	Acute systemic effects	260 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term local effects	221 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term systemic effects	14,8 mg/m <sup>3</sup>
	Consumers	Inhalation	Acute local effects	260 mg/m <sup>3</sup>
	Consumers	Dermal	Long-term systemic effects	108 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	16 mg/kg bw/day
	Workers	Dermal	Long-term systemic effects	180 mg/kg bw/day

### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
reaction mixture of ethylbenzene, m-xylene and p-xylene	Soil	2,31 mg/kg dry weight (d.w.)
	Marine water	0,327 mg/l
	Fresh water	0,327 mg/l
	Marine sediment	12,46 mg/kg dry weight (d.w.)
	Fresh water sediment	12,46 mg/kg dry weight (d.w.)
	Sewage treatment plant	6,58 mg/l
	Intermittent use/release	0,327 mg/l
2-methylpropan-1-ol	Soil	0,0765 mg/kg dry weight (d.w.)
	Marine water	0,04 mg/l
	Fresh water	0,4 mg/l
	Marine sediment	0,156 mg/kg dry weight (d.w.)
	Fresh water sediment	1,56 mg/kg dry weight (d.w.)
	Sewage treatment plant	10 mg/l
	Intermittent use/release	11 mg/l

## 8.2 Exposure controls

### Personal protective equipment

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## THINNER 10

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10.01.2025	MAT0GE00_021 HR/EN	Date of first issue: 10.01.2025

---

Eye/face protection	:	Equipment should conform to EN 166 Eye wash bottle with pure water Tightly fitting safety goggles Wear face-shield and protective suit for abnormal processing problems.
Hand protection	:	
Remarks	:	Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.
Skin and body protection	:	Impervious clothing Choose body protection according to the amount and concentration of the dangerous substance at the work place.

---

### SECTION 9: Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

Physical state	:	liquid
Colour	:	colourless
Odour	:	characteristic
Odour Threshold	:	No data available
Melting point/freezing point	:	-108,0 °C (calculation method (principal components, lowest value))
Boiling point/boiling range	:	108 °C (calculation method (principal components, lowest value))
Upper explosion limit / Upper flammability limit	:	12 %(V) (calculation method (principal components, highest value))
Lower explosion limit / Lower flammability limit	:	1,1 %(V) (calculation method (principal components, highest value))
Flash point	:	25 °C(calculation method (principal components, lowest value))
Ignition temperature	:	415 °C(calculation method (principal components, highest value))
Decomposition temperature	:	No decomposition if stored and applied as directed.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## THINNER 10

Version 1.0	Revision Date: 10.01.2025	SDS Number: MAT0GE00_021 HR/EN	Date of last issue: - Date of first issue: 10.01.2025
----------------	------------------------------	--------------------------------------	--

---

Hazardous decomposition products formed under fire conditions.

pH : No data available

### Solubility(ies)

Water solubility : immiscible

Solubility in other solvents : Description: miscible with most organic solvents

Partition coefficient: n-octanol/water : log Pow: 2,77 - 3,15(calculation method (principal components, highest value))

Vapour pressure : 4 - 40 hPa(calculation method (principal components, highest value))  
(20 °C)

Relative density : 0,85(calculation method (principal components, highest value))

Density : 0,845 - 0,849 g/cm<sup>3</sup> (23 °C)

Relative vapour density : 2,55(calculation method (principal components, lowest value))  
(Air = 1.0)

### 9.2 Other information

No data available

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No decomposition if stored and applied as directed.

### 10.2 Chemical stability

No decomposition if stored and applied as directed.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.

Vapours may form explosive mixture with air.

### 10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

### 10.5 Incompatible materials

Materials to avoid : Not applicable

---

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## THINNER 10

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10.01.2025	MAT0GE00_021 HR/EN	Date of first issue: 10.01.2025

---

### 10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

---

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

##### Product:

Acute inhalation toxicity : Acute toxicity estimate: 14,47 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: 1.448 mg/kg  
Method: Calculation method

##### Components:

#### reaction mixture of ethylbenzene, m-xylene and p-xylene:

Acute oral toxicity : LD50 Oral (Rat):  $\geq$  8.700 mg/kg

Acute inhalation toxicity : LC50 (Rat): 27,14 mg/l  
Test atmosphere: vapour

Acute dermal toxicity : Assessment: The component/mixture is moderately toxic after single contact with skin.

#### 2-methylpropan-1-ol:

Acute oral toxicity : LD50 Oral (Rat):  $\geq$  2.460 mg/kg

Acute dermal toxicity : LD50 (Rabbit):  $\geq$  3.400 mg/kg

#### Skin corrosion/irritation

##### Product:

Remarks : Extremely corrosive and destructive to tissue.

##### Components:

#### reaction mixture of ethylbenzene, m-xylene and p-xylene:

Result : irritating

#### 2-methylpropan-1-ol:

Result : irritating

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## THINNER 10

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10.01.2025	MAT0GE00_021 HR/EN	Date of first issue: 10.01.2025

---

### Serious eye damage/eye irritation

#### Product:

Remarks : May cause irreversible eye damage.

#### Components:

##### reaction mixture of ethylbenzene, m-xylene and p-xylene:

Result : Eye irritation

##### 2-methylpropan-1-ol:

Result : Corrosive

### STOT - single exposure

#### Components:

##### reaction mixture of ethylbenzene, m-xylene and p-xylene:

Assessment : May cause respiratory irritation.

##### 2-methylpropan-1-ol:

Assessment : May cause drowsiness or dizziness.

Assessment : May cause respiratory irritation.

### STOT - repeated exposure

#### Components:

##### reaction mixture of ethylbenzene, m-xylene and p-xylene:

Assessment : May cause damage to organs through prolonged or repeated exposure.

### Aspiration toxicity

#### Components:

##### reaction mixture of ethylbenzene, m-xylene and p-xylene:

May be fatal if swallowed and enters airways.

## 11.2 Information on other hazards

### Endocrine disrupting properties

#### Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## THINNER 10

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10.01.2025	MAT0GE00_021 HR/EN	Date of first issue: 10.01.2025

(EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### Further information

#### Product:

Remarks : Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.  
Concentrations substantially above the TLV value may cause narcotic effects.  
Solvents may degrease the skin.

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Components:

##### **reaction mixture of ethylbenzene, m-xylene and p-xylene:**

Toxicity to fish : LC50 (Fish):  $\geq 1 - 10$  mg/l  
Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia (water flea)):  $\geq 1 - 10$  mg/l  
Toxicity to microorganisms : EC50 (Bacteria):  $\geq 1 - 100$  mg/l

##### **2-methylpropan-1-ol:**

Toxicity to fish : LC50 (Fish):  $> 100$  mg/l  
Exposure time: 96 h

### 12.2 Persistence and degradability

#### Components:

##### **reaction mixture of ethylbenzene, m-xylene and p-xylene:**

Biodegradability : Readily biodegradable.  
Photodegradation : Decomposes rapidly in contact with light.

##### **2-methylpropan-1-ol:**

Biodegradability : Result: Biodegradable

### 12.3 Bioaccumulative potential

#### Components:

##### **reaction mixture of ethylbenzene, m-xylene and p-xylene:**

Bioaccumulation : Bioconcentration factor (BCF): 25,9  
Bioaccumulation is unlikely.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## THINNER 10

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10.01.2025	MAT0GE00_021 HR/EN	Date of first issue: 10.01.2025

---

Partition coefficient: n-octanol/water : log Pow: 2,77 - 3,15

### **2-methylpropan-1-ol:**

Partition coefficient: n-octanol/water : log Pow: 0,79

### 12.4 Mobility in soil

#### **Components:**

#### **reaction mixture of ethylbenzene, m-xylene and p-xylene:**

Distribution among environmental compartments : Koc: 537, log Koc: 2,73  
Moderately mobile in soils  
The product evaporates from soil.

Stability in soil : Dissipation time: 23 d  
Percentage dissipation: 50 % (DT50)

### 12.5 Results of PBT and vPvB assessment

#### **Product:**

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

### 12.6 Endocrine disrupting properties

#### **Product:**

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### 12.7 Other adverse effects

#### **Product:**

Additional ecological information : No data available

---

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product : Do not dispose of waste into sewer.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## THINNER 10

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10.01.2025	MAT0GE00_021 HR/EN	Date of first issue: 10.01.2025

Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.

Waste Code : 08 01 11, waste paint and varnish containing organic solvents  
or other hazardous substances

### SECTION 14: Transport information

#### 14.1 UN number or ID number

ADN	: UN 1263
ADR	: UN 1263
RID	: UN 1263
IMDG	: UN 1263
IATA	: UN 1263

#### 14.2 UN proper shipping name

ADN	: PAINT RELATED MATERIAL (reaction mixture of ethylbenzene, m-xylene and p-xylene, ISOBUTANOL)
ADR	: PAINT RELATED MATERIAL (reaction mixture of ethylbenzene, m-xylene and p-xylene, ISOBUTANOL)
RID	: PAINT RELATED MATERIAL (reaction mixture of ethylbenzene, m-xylene and p-xylene, ISOBUTANOL)
IMDG	: PAINT RELATED MATERIAL (reaction mixture of ethylbenzene, m-xylene and p-xylene, ISOBUTANOL)
IATA	: Paint related material (reaction mixture of ethylbenzene, m-xylene and p-xylene, ISOBUTANOL)

#### 14.3 Transport hazard class(es)

	Class	Subsidiary risks
ADN	: 3	
ADR	: 3	
RID	: 3	
IMDG	: 3	
IATA	: 3	

#### 14.4 Packing group

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## THINNER 10

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10.01.2025	MAT0GE00_021 HR/EN	Date of first issue: 10.01.2025

---

### ADN

Packing group : II  
Classification Code : F1  
Hazard Identification Number : 33  
Labels : 3

### ADR

Packing group : II  
Classification Code : F1  
Hazard Identification Number : 33  
Labels : 3  
Tunnel restriction code : (D/E)

### RID

Packing group : II  
Classification Code : F1  
Hazard Identification Number : 33  
Labels : 3

### IMDG

Packing group : II  
Labels : 3  
EmS Code : F-E, S-E

### IATA (Cargo)

Packing instruction (cargo aircraft) : 364  
Packing instruction (LQ) : Y341  
Packing group : II  
Labels : Flammable Liquids

### IATA (Passenger)

Packing instruction (passenger aircraft) : 353  
Packing instruction (LQ) : Y341  
Packing group : II  
Labels : Flammable Liquids

## 14.5 Environmental hazards

### ADN

Environmentally hazardous : no

### ADR

Environmentally hazardous : no

### RID

Environmentally hazardous : no

### IMDG

Marine pollutant : no

## 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## THINNER 10

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10.01.2025	MAT0GE00_021 HR/EN	Date of first issue: 10.01.2025

Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. P5c FLAMMABLE LIQUIDS

### 15.2 Chemical safety assessment

A Chemical Safety Assessment is not required for this substance.

## SECTION 16: Other information

### Full text of H-Statements

H226	:	Flammable liquid and vapour.
H304	:	May be fatal if swallowed and enters airways.
H312	:	Harmful in contact with skin.
H315	:	Causes skin irritation.
H318	:	Causes serious eye damage.
H319	:	Causes serious eye irritation.
H332	:	Harmful if inhaled.
H335	:	May cause respiratory irritation.
H336	:	May cause drowsiness or dizziness.
H373	:	May cause damage to organs through prolonged or repeated exposure.

### Full text of other abbreviations

Acute Tox.	:	Acute toxicity
Asp. Tox.	:	Aspiration hazard
Eye Dam.	:	Serious eye damage
Eye Irrit.	:	Eye irritation
Flam. Liq.	:	Flammable liquids
Skin Irrit.	:	Skin irritation
STOT RE	:	Specific target organ toxicity - repeated exposure
STOT SE	:	Specific target organ toxicity - single exposure
2000/39/EC	:	Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
HR BEI	:	Croatia. Biological Exposure Limits
HR OEL	:	Croatia. Regulations on limit values for exposure to hazardous substances at work and on the biological limit values.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## THINNER 10

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10.01.2025	MAT0GE00_021 HR/EN	Date of first issue: 10.01.2025

2000/39/EC / TWA	:	Limit Value - eight hours
2000/39/EC / STEL	:	Short term exposure limit
HR OEL / STEL	:	Short term exposure limit
HR OEL / GVI	:	time weighted average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Further information

#### Classification of the mixture:

Flam. Liq. 2	H225
Acute Tox. 4	H332
Acute Tox. 4	H312
Skin Irrit. 2	H315
Eye Dam. 1	H318
STOT SE 3	H336
STOT SE 3	H335
STOT RE 2	H373

#### Classification procedure:

Based on product data or assessment  
Calculation method  
Calculation method  
Calculation method  
Calculation method  
Calculation method  
Calculation method  
Calculation method

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## THINNER 10

Version 1.0	Revision Date: 10.01.2025	SDS Number: MAT0GE00_021 HR/EN	Date of last issue: - Date of first issue: 10.01.2025
----------------	------------------------------	--------------------------------------	--

---

Asp. Tox. 1

H304

Calculation method

Material codes (bulk) for  
which the SDS is valid 430539 ,

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.