

# FASADEX QUARTZ GRUND

**Fasadex**<sup>®</sup>



## TYPE OF PRODUCT

Fasadex quartz grund is a primer based on synthetic resin, mineral filler and additives..

## APPLICATION AREA

For preparing smooth concrete as well as for finished concrete surfaces prior to applying cement, lime cement and gypsum plaster.  
For indoor and outdoor applications.

## SURFACE PREPARATION

Substrate must be clean, free from dust, oil and grease. Weak areas, voids cement laitance must be removed back to a sound substrate.

The concrete must be at least 3 months old (with a maximum of 3,0% residual moisture).

The gypsum-lime mortars must be at least 21 days old.

## APPLICATION INSTRUCTION

Stir the Fasadex quartz grund just before use. Apply one coat undiluted Fasadex quartz grund uniformly to the substrate using a roller or brush, ensuring that a continuous coat is achieved over the entire surface. After use wash tools immediately with clean water. Any remaining residues once dry have to be removed mechanically or with Luxal Nitro thinner. Attention: Luxal Nitro thinner is flammable.

## DRYING TIME

Min 12-24 hours, under the normal conditions. Drying time depends on temperature and relative humidity.

## MASS DENSITY

1500 kg/m<sup>3</sup>.

## SOLID CONTENT

56-57 % by weight.

## VISCOSITY

3 500-5 500 mPas (RVT ISO 2555).

Last update: March 2022.

Limitation of Liability. The information in this data sheet is based upon laboratory tests we believe to be accurate and is intended for guidance only. All recommendations or suggestions relating to the use of the products made by Chromos, whether in technical documentation or in response to specific enquiry or otherwise are based on data which to the best of our knowledge are reliable. It is end user's responsibility to determine the suitability of the product for its intended use. Producer has no control over either the quality or condition of the substrate, or the many factors affecting the use and application of the product. Chromos does therefore not accept any liability arising from loss, injury or damage resulting from such use. The data contained herein are liable to modification as result of practical experience and continuous product development.

**Chromos boje i lakovi d.d.**  
Radnička cesta 173d  
10000 Zagreb, Hrvatska

Phone: +385 1 2410 666  
Fax: +385 1 2405 512  
www.chromos.eu



**Fasadex**<sup>®</sup>



#### APPEARANCE

Rough, matt.

#### COLOUR

Red.

#### APPLICATION TEMPERATURE

From +5°C to +30°C.

#### SPREADING RATE

0,25-0,30 kg/m<sup>2</sup>

The consumption of Fasadex quartz grund depends on the porosity and absorption of the surface.

#### PACKAGING

Plastic drum à 5 kg and 20 kg.

#### STORAGE

In dry and good ventilated space at temperatures from +5°C to +35°C.

Shelf life: 24 months, in its original unopened packaging. Keep from freezing and direct sun light.

#### DISPOSAL

Empty packaging completely and dispose of in accordance with regulations. For the disposal of product residues, waste water and containers with adherent product residues please follow the local governmental regulations.

#### SAFETY PRECAUTIONS

See relevant material safety data sheet and label.

Last update: March 2022.

Limitation of Liability. The information in this data sheet is based upon laboratory tests we believe to be accurate and is intended for guidance only. All recommendations or suggestions relating to the use of the products made by Chromos, whether in technical documentation or in response to specific enquiry or otherwise are based on data which to the best of our knowledge are reliable. It is end user's responsibility to determine the suitability of the product for its intended use. Producer has no control over either the quality or condition of the substrate, or the many factors affecting the use and application of the product. Chromos does therefore not accept any liability arising from loss, injury or damage resulting from such use. The data contained herein are liable to modification as result of practical experience and continuous product development.

**Chromos boje i lakovi d.d.**  
Radnička cesta 173d  
10000 Zagreb, Hrvatska

Phone: +385 1 2410 666  
Fax: +385 1 2405 512  
www.chromos.eu

